

IBM Storage Networking SAN128B-7

Highlights

- Provide high scalability with 128 ports in a 2U switch
 - Automate repetitive, administrative tasks
 - Maximize SCSI, NVMe and high transaction workloads with lower latency
 - Enable pay-as-you-grow scalability from 28 to 128 ports at 64G
 - Simplify troubleshooting by identifying and isolating issues
 - Safeguard mission-critical workloads
 - Visualize SAN health and performance data
-

Create Large Fabrics in Less Rack Space with the Highest-Density 64G Switch

Organizations are under pressure to maximize the performance, productivity, and efficiency of their storage investments and resources, even as they rapidly scale their environments and protect against disruptions, outages, and cybersecurity vulnerabilities. To address these requirements and the demands of an always-on data center, it is essential for organizations to deploy a modernized infrastructure that provides a faster, more intelligent, and more resilient network. With unmatched performance, integrated security, and automated SAN management technologies, IBM b-type Gen 7 products transform current storage networks into an autonomous SAN and safeguard it against cybersecurity and business-continuity challenges that threaten to disrupt data center operations.

The IBM Storage Networking SAN128B-7 with enhanced security and autonomous SAN technology takes the guesswork out of protecting and managing a network. The SAN128B-7 Switch enables a cyber-resilient network that protects against security threats, enables nonstop operations, and maximizes management automation.

With integrated security technology, the SAN128B-7 protects mission-critical operations by validating the integrity of Gen 7 hardware and software and reduces the vulnerabilities from malware and hijacking by hardening Fabric OS (FOS) and strengthening hardware.

The IBM SAN128B-7 Switch is a 128-port Gen 7 high-density building block in only 2U rack space which enables dense rackmount environments to connect more devices, build larger fabrics, and allow organizations to create high-scale fabrics in less space.

To simplify operations, the SAN128B-7 includes Fabric Vision® technology to monitor and analyze the SAN. This technology provides visibility and insight to quickly identify problems and achieve critical service-level agreements (SLAs). To streamline management workflows, organizations can leverage IBM® SANnav Management Portal to accelerate the deployment of new applications, switches, servers, and storage. Furthermore, a modernized graphical user interface (GUI) improves operational efficiencies with visual dashboards for instant visibility and faster troubleshooting.

Build High-Performance, Multi-Protocol Fabrics

The SAN128B-7 is designed for maximum flexibility and value. This enterprise-class switch offers pay-as-you-grow scalability with Ports on Demand (POD). Organizations can quickly and cost-effectively scale from 48 ports to 128 ports to support growth. The IBM SAN128B-7 provides 96 ports that support 64G, 32G, 16G, 8G SFP+ optics and 16 ports that support the same SFP+ optics or new SFP-DD (double density) optics for 2x64G, 2x32G, 2x16G for device or ISL connections. The SAN128B-7 base configuration comes with 48 ports enabled and can scale to 128 ports by installing SFP and SFP-DD POD licenses in any order and any combination.

The SAN128B-7 Switch supports SCSI and NVMe over Fibre Channel, enabling organizations to integrate IBM® b-type Fibre Channel networks with next-generation flash storage, without a disruptive rip-and-replace. This enables enterprises to achieve faster application response times and harness the performance of new storage technologies to deliver the performance, application response time, and scalability needed for next-generation data centers.

Protect Mission-Critical Workloads with Gen 7 Integrated Security

The volume of cybercriminal behavior has increased as a direct result of the added reliance on digital data by businesses and has caused billions of dollars in losses across all industries. An IBM Gen 7 b-type cyber-resilient storage network helps protect against security threats, enable nonstop operations, and maximize management automation. Fibre Channel fabrics are secure by design based on controlled access between servers and storage and isolation within the data center. IBM Gen 7 technology further reduces the risk of vulnerabilities from malware and hijacking by validating the integrity of the switch operating system, security settings, and hardware.

The IBM b-type Fabric OS® (FOS) adds additional security enhancements to validate the integrity and security of b-type hardware and software. These features include Secure Boot, Trusted FOS (TruFOS) Certificates, FOS hardening with removal of root access, and automated distribution of SSL certificates via SANnav Management Portal. These features ensure that enterprises running IBM b-type directors and switches are currently covered with support and securely enabled to perform critical operations without having to worry about whether the operating system has been tampered with. In addition, the FOS has been hardened by removing root-level access to the operating system to protect the SAN against malware and hijacking attacks.

Those enterprises using the IBM® SANnav™ Management Portal have the ability to automatically distribute SSL certificates across the SAN to ensure authenticity and encryption settings. With SANnav, administrators can set up monitoring and alerting for security configuration changes, customize security thresholds, give proper access control to individual admins, and view switch security events.

Autonomous SAN Innovation

The SAN128B-7 Switch with Fabric Vision technology provides a robust analytics architecture that delivers autonomous SAN technology through self-learning, self-optimizing, and self-healing capabilities. IBM® b-type Fabric Vision technology is a suite of features that leverage comprehensive data collection capabilities with powerful analytics to quickly understand the health and performance of the environment and identify any potential impacts or trending problems.

Automate the SAN to Simplify Management Complexity

IT organizations spend nearly half of their time performing repetitive daily management tasks, such as zoning, inventory reporting, and operational validation checks. By automating these repetitive tasks, IT administrators can significantly improve their efficiency and dramatically decrease the risk of operational mistakes. Automation in large-scale IT environments integrates diverse infrastructure components with consistency and predictability to deliver greater operational efficiency and agility. The SAN128B-7 Switch can automate actions to simplify management and resolve issues without intervention to avoid network disruptions and outages. Through open DevOps automation technology, organizations can reliably perform resource-intensive tasks, such as infrastructure deployment and provisioning, in a fraction of the time to expedite IT services while eliminating human error. In addition, automation proactively monitors the network to self-optimize performance and automatically mitigate fabric-related issues with self-healing capabilities.

With self-optimizing capabilities, IBM® b-type utilizes actionable intelligence to maximize performance. Real-time monitoring of health and performance characteristics enables the network to make smarter decisions on traffic prioritization, congestion management, and notification to ensure optimal network performance for applications and storage. IBM b-type Gen 7 Traffic Optimizer guarantees critical application performance by automatically prioritizing traffic, such as protocol, speed, and latency. In addition, Traffic Optimizer can help avoid application performance impacts by automatically isolating traffic that is adversely impacting other flows.

IBM® Gen 7 raises the bar for network availability through automatic avoidance and recovery features, delivering a self-healing SAN. When potential disruptions are detected, the network will automatically mitigate or resolve issues without intervention. The Fabric OS (FOS) software identifies abnormal or unexpected behavior and automatically takes action to avoid degradation in performance. If congestion occurs, the software instantly notifies end devices of the congestion problem through an alerting and signaling process. Once the end devices are alerted, the software ensures data delivery with automatic failover or adjustment of traffic to mitigate the impact of the problem. IBM® SANnav management tools can identify various latency severity levels, pinpointing exactly which devices are causing the issues or which devices are impacted by a bottleneck, and they can quarantine misbehaving devices automatically.

Instant Visibility with IBM SANnav

IBM® SANnav Management Portal and SANnav Global View empower IT administrators with comprehensive visibility across the entire SAN, from a global view down to local environments. SANnav contextualizes data into visual dashboards and topology views, which allows administrators to quickly detect and isolate points of interest to increase operational efficiencies. In addition, IBM® SANnav streamlines management workflows to accelerate the deployment of new applications, switches, servers, and storage.

SAN64B-7 System Architecture

Product Number	8969-P96 - Switch with non-port side intake, port side exhaust (back to front air flow) 8969-R96 – Switch with port side intake, non-port side exhaust (front to back air flow)
Fibre Channel ports	128 ports (96 64G SFP+ ports, plus 16 2x64G SFP-DD ports), each supporting E_Ports, M_Ports, F_Ports, D_Ports, EX_Ports. 48 -port base configuration; additional ports are enabled with two 24-port SFP+ PODs (Ports on Demand), plus a 32-port SFP-DD POD (with 16 2x64G SFP-DD transceivers), scaling the switch from 48 ports to 128 ports.
Scalability	Full-fabric architecture with a maximum of 239 switches.
Certified maximum	4K active nodes; 56 switches, 19 hops in Fabric OS® fabrics
Performance	Fibre Channel: 8.5Gb/s line speed, full duplex; 10.53Gb/s line speed, full duplex; 14.025Gb/s line speed, full duplex; 28.05Gb/s line speed, full duplex; 57.8Gb/s line speed, full duplex; auto-sensing of 8, 10, 16, 32, and 64G FC port speeds. 10G optionally programmable to fixed port speed.
Load balancing	Frame-based ISL Trunking load balances up to eight SFP+ ports per ISL trunk; up to 512Gb/s per ISL trunk when using 64G optics. Dynamic Path Selection (DPS) provides exchange-based load balancing across all available ISLs.
Aggregate bandwidth	8.192Tb/s
Maximum fabric latency	Latency for locally switched ports is 460 ns (including FEC).
Maximum frame size	2112-byte payload
Frame buffers	24K per switching ASIC
Classes of service	Class 2, Class 3, Class F (inter-switch frames)
Port types	D_Port (ClearLink® Diagnostic Port), E_Port, EX_Port, F_Port; optional port-type control AccessGateway mode: F_Port and NPIV-enabled N_Port
Data traffic types	Fabric switches supporting unicast.
Media types	64G: Hot-pluggable SFP+, LC connector: SWL, LWL 10 km, ELWL 25 km. 32G: Hot-pluggable SFP+, LC connector: SWL, LWL 10 km, ELWL 25 km. 10G: Hot-pluggable SFP+, LC connector: SWL, LWL 10 km. 2x64G: Hot-pluggable SFP-DD, SN connector: SWL Fibre Channel distance is subject to fiber-optic cable and port speed.
USB	One standard USB port for firmware download, SupportSave, and configuration upload or download.
Fabric Services	Fabric Vision; Monitoring and Alerting Policy Suite (MAPS); Flow Vision; Adaptive Networking (QoS); Fabric Performance Impact (FPI) Monitoring; Slow Drain Device Quarantine (SDDQ); Advanced Zoning (default zoning, port/WWN zoning, broadcast zoning, peer zoning, target-driven zoning); Dynamic Fabric Provisioning (DFP); Dynamic Path Selection (DPS); Extended Fabrics; Enhanced BB Credit Recovery; FDMI; Frame Redirection; Frame-based Trunking; FSPF; Integrated Routing; IPoFC; ISL Trunking; Management Server; Name Server; NPIV; Time Server; Registered State Change Notification (RSCN); Slow Drain Device Quarantine (SDDQ); Reliable Commit Service (RCS); Virtual Fabrics (Logical Switch, Logical Fabric); VMID+; AppServer; Read Diagnostics Parameter (RDP).
Extension	Fibre Channel, in-flight compression (LZO) and encryption (AES-GCM-256); integrated optional 10G Fibre Channel for DWDM MAN connectivity.
FICON	FICON is not supported on SAN128B-7. FICON traffic is supported on the IBM SAN64B-7, SAN256B-7, and SAN512B-7 products.

Management

Supported management software	Brocade Advanced Web Tools; Brocade SANnav Management Portal and SANnav Global View; Command Line Interface (CLI); EZSwitchSetup; HTTP/HTTPS; RESTful API; SNMP v1/v3 (FE MIB, FC Management MIB); SSH.
Security	DH-CHAP (between switches and end devices); FCAP switch authentication; HTTPS; IP filtering; LDAP with IPv6; OpenLDAP; Port Binding; RADIUS; TACACS+; user-defined Role-Based Access Control (RBAC); Secure Copy (SCP); Secure Syslog; SFTP; SSH v2; SSL; Switch Binding; Trusted Switch.
Management Access	10/100/1000Mb/s Ethernet (RJ-45) port, and serial console port (mini-USB).
Diagnostics	ClearLink optics and cable diagnostics, including electrical/optical loopback, link traffic/latency/ distance; flow mirroring; built-in flow generator; POST and embedded online/offline diagnostics, including environmental monitoring; FCping and Pathinfo (FC traceroute); frame viewer; non-disruptive daemon restart; opticshealth monitoring; power monitoring; RAstrace logging; and Rolling Reboot Detection (RRD).

Mechanical

Enclosure	Front-to-back airflow; non-port-side exhaust; power from back, 2U Back-to-front airflow; non-port-side intake; power from back, 2U
Size	Width: 440.00 mm (17.32 in.) Height: 86.7 mm (3.41 in.) Depth: 609.6 mm (24.00 in.)
System Weight	18.92 kg (41.71 lbs) with two power supply FRUs and three fan FRUs, without transceivers

Environment

Operating environment	Temperature: 0°C to 40°C (32°F to 104°F) Humidity: 8% to 90% (non-condensing)
Non-operating environment	Temperature: -25°C to 70°C (-13°F to 158°F) Humidity: 8% to 90% (non-condensing)
Operating Altitude	Up to 3000 m (9842 ft)
Storage altitude	Up to 12 km (39,370 ft)
Shock	Operating: Up to 20G, 6 ms half-sine Non-operating: Half-sine, 33G, 11 ms, 3/eg axis
Vibration	Operating: 0.25 Grms sine, 0.40 Grms random, 5 Hz to 500 Hz Non-operating: 5 Hz at 0.50 Grms; 10–500 Hz at 1.00 Grms (sine vibration); 3–500 Hz at 1.12 Grms (random vibration)
Heat dissipation	128 ports at 3195 Btu/hr

Power

Power supply	Dual, hot-swappable, redundant power supplies with integral cooling fans and status LEDs. 80 Plus Gold
AC input	90V to 264V, 4.5A
AC input linefrequency	50 Hz to 60 Hz nominal, 47 Hz to 63 Hz range
AC power consumption	969W with all 128 ports operating at 64G (96 ports populated with 64G SWL transceivers, 16 ports populated SFP-DD SWL transceivers, each providing two ports of 64G connectivity). 364W for an empty chassis with no optics

Warranty

Warranty	<p>1-year limited warranty</p> <ul style="list-style-type: none"> • 9 x 5 on-site limited support <p>Upgradeable to IBM Storage Expert Care:</p> <p>IBM Storage Expert Care Basic</p> <ul style="list-style-type: none"> • Extended 9 x 5 on-site hardware support for the duration of the contract • License machine code subscription and support for the duration of the contract • Guidance on installation, usage and configuration • Automated ticket management and alerting <p>IBM Storage Expert Care Advanced</p> <ul style="list-style-type: none"> • Extended 24 x 7 on-site hardware support for the duration of the contract • License machine code subscription and support for the duration of the contract • Guidance on installation, usage and configuration • Automated ticket management and alerting • Predictive issue resolution <p>Expert Care options range from 1 to 5 years</p>
----------	---

Why IBM?

Innovative technology, open standards, excellent performance, and a broad portfolio of proven storage software, hardware and solutions offerings—all backed by IBM with its recognized industry leadership—are just a few of the reasons to consider storage solutions from IBM. In addition, IBM delivers some of the best storage products, technologies, services and solutions in the industry without the complexity of dealing with different hardware and software vendors.

For more information

To learn more about IBM Storage Networking b-type family, please contact your IBM representative or IBM Business Partner or visit:

<https://www.ibm.com/it-infrastructure/storage/san/b-type>

© Copyright IBM Corporation 2021.

IBM, the IBM logo, and ibm.com are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at

<https://www.ibm.com/legal/us/en/copytrade.shtml>, and select third party trademarks that might be referenced in this document is available at

https://www.ibm.com/legal/us/en/copytrade.shtml#section_4.

This document contains information pertaining to the following IBM products which are trademarks and/or registered trademarks of IBM Corporation: IBM®.



All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.